

INTERCHANGEABILITY CHART

SMEDEGAARD "EV" Range and WILO Star-RS and TOP-S Ranges

Wilo Model Ref.	230V	400V	Branch Size mm	Port/Port mm	Smedegaard Model Ref.	Notes
SINGLE PUMPS						
Star-RS25/2	*		25	180	EV2-65-2CS (180)	or EV2-65-2CS +2 Adaptors
Star-RS30/2	*		32	180	EV3-65-2CS	
Star-RS25/4	*		25	180	EV2-65-2CS (180)	or EV2-65-2CS +2 Adaptors
Star-RS30/4	*		32	180	EV3-65-2CS	
Star-RS25/6	*		25	180	EV2-70-2CS	
Star-RS30/6	*		32	180	EV3-70-2CS	
Star-RSL25/6	*		25	180	EV2-70-2CS	
TOP-S25/7	*		25	180	EV2-70-2CS	
TOP-S25/7		*	25	180	EV2-75-2CT	
TOP-S30/7	*	*	32	180	EV3-72-2C (S or T)	
TOP-S30/10	*	*	32	180	EV3-100-2C (S or T)	
TOP-S40/4	*	*	40	250	EV4-60-2C (S or T)	
TOP-S40/7	*	*	40	250	EV4-75-2C (S or T)	
TOP-S40/10	*	*	40	250	EV4-95-2C (S or T)	
TOP-S50/4	*	*	50	280	EV5-125-4C (S or T)	
TOP-S50/7	*	*	50	280	EV5-88-2C (S or T)	
TOP-S50/10		*	50	280	EV5-95-2CT	
TOP-S65/7		*	65	280	EV5-95-2CT	
TOP-S65/10		*	65	340	EV6-95-2CT	
TOP-S65/13		*	65	340	EV6-110-2CT	
TOP-S80/7		*	80	360	EV8-95-2CT	
TOP-S80/10		*	80	360	EV8-100-2CT	
TOP-S100/10		*	100	360	EV8-100-2CT	Same length but different flange size
TWIN PUMPS						
Star-RSD30/4	*		32	180	EV3-65-2CDS	
Star-RSD30/6	*		32	180	EV3-70-2CDS	
TOP-SD32/7	*	*	32	180	EV3-72-2CD (S or T)	
TOP-SD40/7	*	*	40	250	EV4-75-2CD (S or T)	
TOP-SD40/10		*	40	250	EV4-95-2CDT	
TOP-SD50/7		*	50	280	EV5-88-2CDT	
TOP-SD50/10		*	50	280	EV5-95-2CDT	
TOP-SD65/10		*	65	340	EV6-95-2CDT	
TOP-SD65/13		*	65	340	EV6-110-2CDT	
TOP-SD80/10		*	80	360	EV8-100-2CDT	

We reserve the right to change specifications.

2001-10-17